

ANTIGRIPPANTE

SPECIAL LUBRICANT SPRAY

Characteristics

Base: Mixture of lubricant oils

Propellant: Denatured and odourless hydrocarbon. Appearance: Amber oil, high viscosity and stringy

Temperature resistance: -10°C / +210°C. Water resistance: Very Good High Oxidation Resistance:

CFC free

Properties:

- High lubricant properties, With EP additive
- With anti-drop additive

Description

ANTIGRIPPANTE is a universal and high adhesive lubricant resists to strong frictions, particularly indicated as a lubricant for mechanical joints. It resists to water and atmospherically agents, the temperatures of use vary from -10 °C to + 210 °C.

It is used to lubricate industrial assembly lines, machines for plastic materials moulding, plugs, reduction gears, guides, mechanical movements, joints, locks, chains, hinges, component subjected to high stresses, chains of motorcycles and mechanical parts in movement which need to be lubricated with a very adhesive product.

Instructions of use

Clean the surfaces to treat.

Shake the can before using and spray the product at brief intervals from a 15 cm distance. The product has a special valve with a tub that permits to reach even the most difficult parts.

Packaging

Spray Aerosol ml 500 Box 25 Aerosol Product Code 10710/05

Head office and Production

Siliconi Commerciale® SpA Via Francia 4 36053 Gambellara Vicenza – ITALY phone + 39.0444.649766 fax +39.0444.440018 e. mail: info@siliconi.it

www.siliconi.it

Production since 1957

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification.

. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.